


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : A61C 13/00		A1	(11) International Publication Number: WO 98/51232
		(43) International Publication Date: 19 November 1998 (19.11.98)	
(21) International Application Number: PCT/SE98/00835		(81) Designated States: AU, CA, JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 7 May 1998 (07.05.98)		Published <i>With international search report.</i> <i>In English translation (filed in Swedish).</i>	
(30) Priority Data: 9701824-6 16 May 1997 (16.05.97) SE			
(71) Applicant (for all designated States except US): NOBEL BIOCARE AB [SE/SE]; P.O. Box 5190, S-402 26 Göteborg (SE).			
(72) Inventors; and (75) Inventors/Applicants (for US only): BÄCK, Tomas [SE/SE]; Kroksläts Parkgata 13, S-431 68 Mölndal (SE). CARLSSON, Lennart [SE/SE]; Matildebergsgatan 36, S-431 38 Mölndal (SE). PETERSSON, Anders [SE/SE]; Munkebacksgatan 32, S-416 54 Göteborg (SE).			
(74) Agent: OLSSON, Gunnar; Nobel Biocare AB, P.O. Box 5190, S-402 26 Göteborg (SE).			

10020401 121801

(54) Title: METHOD AND ARRANGEMENT FOR PRODUCING ELONGATE SUPPORT ELEMENT AND PRODUCT, AND USE OF THE SUPPORT ELEMENT



(57) Abstract

A method and arrangement for producing elongate support element (4) for replacement structure (9) in jaw (2). The support element is applied to implants in the jaw with great accuracy of fit. Identification information (16) is delivered to computer equipment (15) in which supplementary information (17) is input. With the aid of the said information, the computer equipment extracts control data (19) for milling equipment (20) which mills out the support element from a blank. With the aid of the milling information (19), the milling equipment executes the support element according to the shape determined in the computer equipment. In addition, the information comprises details on the configurations of the said seats and the positioning in the support element material/blank.